


## PRO160DZ

Double zone ageing and service temperature wine cellar

Professional range



- + Capacity: 152 bottles\*:
  - upper part: 63 bottles
  - lower part: 89 bottles
- + Vinotag compatible\*\* 
- + Free standing installation
- + Design: bodyblack door frame
- + Cooling system: compressor
- + Type of cold: air moving system
- + Adjustable temperature ranges of use:
  - upper part: 5°C-12°C
  - lower part: 12°C-20°C
- + Electronic regulation
- + Thermometer with white digital display
- + White LED lights with switch button
- + Humidity control: natural (hygrodynamic concept)
- + 1 glass door, anti-UV treated, 2-layers tempered glass (grey-colored) with lock

### TWO INDEPENDENT TEMPERATURE ZONES

Thanks to its 2 temperature zones with independent adjustment, you can store and bring to tasting temperature several types of wine in the same cellar. The upper zone can hold up to 63 bottles between 5 and 12°C while the lower zone can hold up to 89 bottles between 12 and 20°C.

### TO THE NEAREST DEGREE

Aging cellar commitments: Temperature controlled by an electronic thermometer for adjustment to the nearest degree; Filtration and aeration system (activated carbon filter); Hygrometry controlled between 50 and 80%; Protection against light and anti-vibration system guarantee the good aging of your bottles.

### OPTIMIZED STORAGE

Fitted with 15 sliding steel wire shelves, the PRO160DZ cellar can age up to 152 75 cl Bordeaux type bottles. Ergonomic, the shelves have been designed for a horizontal presentation of the wines which facilitates the reading of the labels and the identification of the bottles. Multi-format, they can receive several types of bottles, and are thus adapted to accommodate Bordeaux, Champenoise and Alsacienne type bottles.



## Eco-responsibility

Our products are manufactured in compliance with European environmental rules. Especially, refrigerant fluid (R600a) doesn't reject neither CFC nor HFC and respect environment.

Energy consumption is calculated based on the result obtained for 24h in standard test conditions. The actual energy consumption depends on the conditions of use and location of the device.

This equipment is designed to be used in an ambient temperature between 16°C-32°C.

This appliance is intended to be used exclusively for the storage of wine.

Alcohol abuse is dangerous for health, please consume in moderation.


\*Capacity given as an indication with 75cl Bordeaux traditional type bottles and measured with 15 shelves. Adding shelves reduce considerably the total capacity.

\*\*Thanks to the Vinotag® application, benefit from a digital register of your wine cellar and be alerted of the peak dates of your wines. In partnership with Vivino, scan your bottle to access its pre-filled wine sheet.

## PRO160DZ

Double zone ageing and service temperature wine cellar

### Professional range



#### > EQUIPMENTS INCLUDED

- 15 sliding wire shelves , metal front
- 2 adjustable feet (height 0.8 cm)
- 1 active charcoal filter
- Anti-vibration system

#### > TECHNICAL CHARACTERISTICS

- Energy class: G
- Annual electrical consumption: 198 kWh
- Climatic class: N
- Noise level: 45 dB
- Voltage: 220-240 V
- Power input: 105 W
- Category: 2 - Wine cellar
- Type of gas: R600a

#### > SAFETY

- **Winter system:** maintains the required temperature of your cellar in case of any ambient temperature drop, ideal during winter
- **Visual and audible alarms:** notify you when your attention is required

#### > VINOTAG® APPLICATION

Free wine cellar management application. Access a virtual representation of your wine cellar and a detailed inventory of its contents.

#### > LOGISTIC DATAS

Gross dimensions (WxDxH cm)	: 63 x 74 x 185
Net dimensions (WxDxH cm)	: 59,5 x 67,5 x 183
Gross weight (kg)	: 119.00
Net weight (kg)	: 112.00
Full truck (pcs)	: 51
Container (pcs)	20' : 27
	40' : 54
	40' HC : 72

Gencod 3541362009180

#### > COMPATIBLE ACCESSORIES

- Active charcoal filter: ref. FCA07